

**AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A short message service switching private branch exchange (PBX) system, comprising:

an office line interface unit of the PBX system that interfaces with office lines;

a voice mail interface unit of the PBX system including a digital signal processor and a memory, the voice mail interface unit converting a first pulse code modulation format short message service signal transmitted from the office line interface unit into short message service data, and converting the short message service data into a format of a terminal that will receive the short message service data;

a control unit of the PBX system that switches a pulse code modulation channel of an office line to which a speech path is coupled into a pulse code modulation channel of ~~a~~ the digital signal processor, and determines a type of the terminal that will receive the short message service data; and

an extension line interface unit of the PBX system that transmits a short message service signal having the format corresponding to the type of the terminal determined by the control unit,

wherein the digital signal processor converts the pulse code modulation format short message service signal transmitted from the office line interface unit into the short message

Reply to Office Action dated March 15, 2007

service data by decoding, the digital signal processor converting the short message service data into a second pulse code modulation format short message service signal when the short message service data is to be transmitted to a single line terminal, and the digital signal processor outputs the short message service data as is when the short message service data is to be transmitted to a digital terminal, the memory storing the short message service data, and

wherein the control unit determines whether a digital signal processor resource of the digital signal processor is available when a speech path is connected, the control unit further waits for a prescribed time until the digital signal processor of the digital signal processor becomes available ~~if~~ when the digital signal processor resource is not available, and finishes a reception of the short message service signal ~~if~~ when the digital signal processor resource ~~is not~~ becomes available ~~until~~ after the prescribed time has elapsed.

2. (Currently Amended) The system of claim 1, wherein the office line interface unit comprises at least one of:

an analog office line interface unit that couples to an analog office line and converts an analog format of ~~an~~ a short message service signal transmitted through the analog office line into a pulse code modulation format; and

an integrated services digital network office line interface unit that couples an integrated services digital network office line and receives a short message service signal of a pulse code modulation format through the integrated services digital network office line.

Reply to Office Action dated March 15, 2007

3. (Canceled)

4. (Currently Amended) The system of claim 1, wherein the extension line interface unit comprises at least one of:

an single line terminal extension line interface unit that couples to ~~an~~ the single line terminal and converts the pulse code modulation format short message service signal into an analog format short message service signal by using a coder/decoder; and

a digital terminal extension line interface unit that couples to ~~a~~ the digital terminal.

5. (Canceled)

6. (Currently Amended) The system of claim ~~[[1]]~~ 2, wherein ~~the office line interface unit comprises:~~

~~an analog office line interface unit that couples an analog office line and converts an analog format of an short message service signal transmitted through the analog office line into a pulse code modulation format; and~~

~~an integrated services digital network office line interface unit that couples an integrated services digital network office line and receives a short message service signal of a pulse code modulation format through the integrated services digital network office line, wherein the voice mail interface unit comprises[[;]]:~~

Reply to Office Action dated March 15, 2007

~~a~~the digital signal processor that converts the first pulse code modulation format short message service signal transmitted from the office line interface unit into the short message service data by decoding, converting the short message service data into ~~a~~the second pulse code modulation format short message service signal when the short message service data is to be transmitted to ~~a~~the single line terminal, and ~~outputting~~outputs the short message service data as is when the short message service data is to be transmitted to ~~a~~the digital terminal, and

~~a~~the memory that stores the short message service data, and wherein the extension line interface unit comprises[[,]]:

~~an~~a single line terminal extension line interface unit that couples to the single line terminal and converts the second pulse code modulation format short message service signal into an analog format short message service signal by using a coder/decoder, and

a digital terminal extension line interface unit that couples to the digital terminal.

7. (Currently Amended) A method for operating a private branch exchange system, comprising:

determining whether a digital signal processor can be detected when an office line and a speech path are connected to each other;

transmitting ~~a~~a short message service signal transmitted from the office line to the digital signal processor when the digital signal processor is detected;

Reply to Office Action dated March 15, 2007

determining an extension line terminal that will receive the short message service signal;

transmitting the short message service signal to the determined extension line terminal from the usable digital signal processor;

waiting for a prescribed detection time when the digital signal processor is not detected; and

finishing a reception of the short message service signal ~~if~~ when the usable digital signal processor ~~does not become available until~~ becomes available after the prescribed detection time has elapsed,

wherein the digital signal processor converts the received short message service signal into short message service data, and generates a short message service message corresponding to the extension line terminal according to a main processor, wherein the usable digital signal processor generates a pulse code modulation format short message service signal when the extension line terminal is a single line terminal, and generates the short message service data when the extension line terminal is a digital terminal.

8. (Canceled)

9. (Original) The method of claim 7, wherein when the office line is a public switched telephone network office line, a switched telephone network office line interface unit converts a frequency shift keying format short message service signal to a pulse code modulation

Reply to Office Action dated March 15, 2007

format short message service signal and transmits the pulse code modulation format short message service signal to the digital signal processor.

10. (Currently Amended) The method of claim 7, wherein when the office line is an integrated services digital network office line, ~~a~~an integrated services digital network office line interface unit transmits a pulse code modulation format short message service signal to the digital signal processor.

11-12. (Canceled)

13. (Currently Amended) The method of claim ~~[[12]]~~ 7, wherein the pulse code modulation format short message service signal is converted into ~~an~~a frequency shift keying format short message service signal by a coder/decoder and the frequency shift keying format short message service signal is transmitted to the single line terminal.

14. (Currently Amended) A method for switching short message service of a private branch exchange (PBX) system, comprising:

switching a pulse code modulation channel of an office line interface unit to a pulse code modulation channel of a digital signal processor if a speech path is connected to the office line interface unit;

Reply to Office Action dated March 15, 2007

transmitting ~~an~~ a short message service signal to the digital signal processor from the office line interface unit through the pulse code modulation channel;

decoding the short message service signal transmitted to the digital signal processor;

switching the pulse code modulation channel of the digital signal processor to a pulse code modulation channel of ~~an~~ a single line terminal extension line interface unit ~~if~~ when an extension line terminal that will receive the short message service signal is ~~an~~ a single line terminal; and

switching ~~an~~ a short message service data channel of the digital signal processor to ~~an~~ a short message service data channel of a digital terminal extension line interface unit ~~if~~ when the extension line terminal that will receive the short message service signal is a digital terminal,

wherein a control unit determines whether a digital signal processor resource of the digital signal processor is available when a speech path is connected, ~~waits~~ the control unit waiting for a prescribed time until the digital signal processor becomes available ~~if~~ when the digital signal processor resource is not available, and finishes a reception of the short message service signal ~~if~~ when the digital signal processor resource ~~is not~~ becomes available ~~until~~ after the prescribed time has elapsed, wherein the digital signal processor is only a single digital signal processor of the PBX system.

15. (Currently Amended) The method of claim 14, wherein when the office line interface unit is a switched telephone network office line interface unit, ~~an~~ a frequency shift

Reply to Office Action dated March 15, 2007

keying format short message service signal transmitted through a switched telephone network office line is converted into a pulse code modulation format short message service signal and the pulse code modulation format short message service signal is transmitted to the digital signal processor.

16. (Currently Amended) The method of claim 14, wherein when a pulse code modulation format short message service signal is transmitted through the pulse code modulation channel of the digital signal processor, the single line terminal extension line interface unit converts the PCM format short message service signal into ~~an~~ a frequency shift keying format short message service signal and transmits the frequency shift keying format short message service signal to ~~an~~ a single line terminal.

17. (Currently Amended) A private branch exchange (PBX) system, comprising:  
a single digital signal processor of the PBX system that receives a short message service signal in a first format and converts the short message service signal into a second format short message service signal; and

a controller of the PBX system that controls the digital signal processor and determines the second format,

wherein the digital signal processor converts the first format short message service signal into the second format short message service signal by converting the first format short message service signal into short message service data and converting the short message service



Reply to Office Action dated March 15, 2007

data to the second format short message service signal, the converting the first format short message service signal into the short message service data comprising decoding, converting the short message service data into the second format short message service signal when the short message service data is transmitted to a single line terminal, and outputting the short message service data as is when the short message service data is transmitted to a digital terminal,

wherein the controller determines whether a digital signal processor resource of the single digital signal processor is available when a speech path is connected, waits for a prescribed time until the digital signal processor becomes available ~~if~~ when the digital signal processor resource is not available, and finishes a reception of the short message service signal in the first format ~~if the digital signal processor resource is not available until~~ after the prescribed time has elapsed and the digital signal processor resource becomes available.

18. (Currently Amended) The system of claim 17, wherein the digital signal processor receives the first format short message service signal in one of an office line of the system and an extension line of the system, and transmits the converted second format short message service signal to the other one of the office line and the extension line.

19. (Currently Amended) The system of claim 18, wherein the single digital signal processor is in a voice mail interface unit.

20. (New) The system of claim 17, wherein the single digital processor performs short message service detection, short message service generation and compressing of voice.

21. (New) The system of claim 1, wherein the digital signal processor comprises only a single digital signal processor.

22. (New) The system of claim 1, wherein the single digital processor performs short message service detection, short message service generation and compressing of voice.

23. (New) The system of claim 1, wherein the extension line interface unit transmits the short message service signal in an analog format when the short message service data is transmitted to the signal line terminal.